



Oil Free Compressors with Dryer



Dental Surgeries Motor HP Volt/Hz Ltrs/Min @ 5bar Receiver Ltrs dB(A) Dimensions LxDxH Weight Kgs

DenComp 3	3	1.5	230/50	150	50	67	75x40x75	60
DenComp 4	4	2.5	230/50	225	50	67.5	75x40x75	62
DenComp 8	8	2x2.5	230/50	450	100	70	120x40x75	124

Low Noise Oil Free Compressors with Dryer

Dental Surgeries Motor HP Volt/Hz Ltrs/Min @ 5bar Receiver Ltrs dB(A) Dimensions LxDxH Weight Kgs

DenComp LN2	2	1.4	230/50	100	30	57	80x40x57	72
DenComp LN3	3	1.5	230/50	150	30	57	92x40x57	76
DenComp LN4	4	2.5	230/50	225	30	57	92x40x57	85

Emergency Backup Compressor

Dental Surgeries Motor HP Volt/Hz Ltrs/Min @ 5 bar Receiver Ltrs dB(A) Dimensions LxDxH Weight Kgs

SuperFox 3T	3	1.5	230/50	160	3	61	55x34x38	19.5
-------------	---	-----	--------	-----	---	----	----------	------

Standard voltage for all compressors 230/50. Other voltages available. Maximum pressure for all compressors 8 bar.

Filtration & Regulation

Port bsp Max Flow Rate l/min Particle Removal Oil Carryover Dimensions LxDxH Weights Kgs

D20XAC Duplex Filter	"1/4"	425	0.01 micron	0.003 ppm	330x75x75	0.85
A20MS Sterile Filter	"1/4"	565	0.01 micron	0.003 ppm	230x75x75	0.65
MSM 1 Filter Regulator	"1/4"	660	5 micron	5 ppm	60x105x180	0.45

Distributed by

"DenComp Equipment Ltd registered office: Argyle Commercial Centre, Unit 5 Argyle St, Swindon, SN2 8AR"
Northern Sales Office Southern Sales Office
Tel 01786 832265 Fax 01786 832265 Tel 01793 639133 Fax 01793 635062
Mobile 07885 200875 Mobile 07740 395045
email: sales.dencomp@ntlworld.com

DenComp Compressors

